CHAPTER 6 OPERATOR EXPOSURE MONITORING (Determining Compliance with 30 C.F.R. §§ 56/57.5002)

Metal/Nonmetal Health Inspection Procedures Handbook

Chapter 6

Tab	Γable of Contents			
I.	Introduction	6-3		
II.	Surveys	6-3		
III.	Frequency of Surveys	6-4		
IV.	Verification	6-5		
V.	Inspection Procedures	6-6		

Chapter 6 Appendices

Table of Contents	Page
Appendix 6A 30 C.F.R. §§ 56/57.5002 Sample Compliance Checklist	6A-1
Appendix 6B Scenarios	6A-2
Appendix 6C Example Citations and Terminations	6A-5

CHAPTER 6 OPERATOR EXPOSURE MONITORING (Determining Compliance with 30 C.F.R. §§ 56/57.5002)

I. Introduction

The standards at 30 C.F.R. §§ 56/57.5002, Exposure Monitoring, is broadly worded and are performance-based requiring an operator to conduct dust, gas, mist, and fume surveys as frequently as necessary to determine the adequacy of control measures. A mine operator has the primary responsibility for protecting the health of miners and must comply with the exposure monitoring standards to ensure that miners are not exposed to harmful concentrations of airborne contaminants.

When determining compliance, the inspector must determine whether surveys are being conducted and, if so, whether the surveys are adequate and conducted as frequently as necessary in a manner consistent with the protective purpose of the standard. The exposure monitoring standards only apply to the airborne contaminants covered under 30 C.F.R. §§ 56/57.5001(a) chemical substances, and (b) asbestos.

Compliance should be evaluated using an objective test: What actions would a reasonably prudent person familiar with all the facts, in particular those specific to the mining industry, take in order to provide the protection intended by the standard?

Consultation with the Agency's Health Specialists and/or Industrial Hygienists is always an option to assist in determining compliance.

II. Surveys

Surveys are defined as any information collection method that:

- Yields information as to a miner's exposure to airborne contaminants, and/or,
- Yields information as to the effectiveness of controls in reducing exposures to airborne contaminants.

The exposure monitoring standards do not specify the type of surveys that operators must conduct. Surveys may be quantitative or qualitative. The following are examples of the different types of surveys that may be conducted by an operator that should be taken into consideration by the inspector when evaluating compliance with sections §§ 56/57.5002. Surveys may be conducted by the operator or may also be conducted by a third party (e.g., consultant, insurance company, etc.). However, any survey or sampling conducted by MSHA cannot be used by the operator to satisfy the requirements of sections §§ 56/57.5002.

1. **Exposure sampling:** exposure sampling is a quantitative survey that provides a measurement of miners' exposures to airborne contaminants. Operators may collect air samples to determine if miners' exposures exceed the threshold limit values (TLVs) in accordance with sections §§ 56/57.5001(a) or the permissible exposure limit (PEL) for asbestos in accordance with sections §§ 56/57.5001(b). Exposure sampling should be conducted in accordance with established scientific principles, such as developed by

MSHA, NIOSH, OSHA, or equivalent sampling and analytical methods. Wipe samples are also a quantitative survey that can provide information about presence of a hazard. Although wipe samples can provide information on potential exposures, they do not provide an actual measurement of exposures to airborne contaminants.

- 2. **Workplace inspection:** a workplace inspection is an example of a qualitative survey and can include a walk-through visual inspection before or during a shift with a focus on observing or identifying potential hazards that can lead to an overexposure to airborne contaminants. For example, if a workplace inspection reveals that a cloud is rising from a processing tank, then a potential for an overexposure to an acid mist may be present.
- 3. **Inspecting equipment and controls:** inspecting equipment and controls to ensure performance is in accordance with the manufacturer's specifications is a type of qualitative survey. This type of survey can include scheduled or routine maintenance of the equipment. This type of survey not only focuses on mining equipment, such as drills, but should also include equipment used to control or reduce exposures. Such equipment includes dust collectors, ventilation systems, and early warning devices.
- 4. **Injury, illness, or incident tracking reports:** an injury, illness, or incident report can be a survey for determining the adequacy of controls because these reports may identify potential exposure to harmful levels of airborne contaminants.
- 5. **Miner input:** a miner who attends or participates in inspections, safety meetings, or interviews and briefings may provide information on possible exposure to harmful levels of airborne contaminants.
- 6. **Occupational health assessment:** occupational health assessments include medical surveillance that can provide information as to potential exposures. Examples include tests for blood lead levels, chest X-rays, spirometry, etc.
- 7. **Other survey methods:** may also be used by the operator to determine whether controls are adequate in protecting miners from harmful exposure to airborne contaminants.

III. Frequency of Surveys

The exposure monitoring standards require that surveys be conducted "as frequently as necessary" to determine the adequacy of the control measures. The following criteria should be taken into consideration by the inspector when evaluating whether surveys are being conducted "as frequently as necessary."

- 1. If either MSHA or operator exposure sampling results are approaching the existing applicable TLV in accordance with sections §§ 56/57.5001(a), or the PEL under sections §§ 56/57.5001(b), then more frequent sampling may be needed.
- 2. A job or equipment change may require an increase in the frequency of inspections. This includes a change in job classification, job task, or personnel; an increase in a production schedule or rate, or an increase in the number of shifts or shift duration; or a change in the equipment used during a job. A change in equipment includes the addition, removal,

- or change to any equipment used to control exposures. For example, if the operator installs a new local exhaust ventilation system (LEV) to reduce exposures to dusts, then more frequent surveys may be required to verify that the system is functioning properly.
- 3. A change in the presence of potential airborne contaminants may require more frequent surveys. In general, this includes a change in the identity, quantity, or physical characteristics of the airborne contaminants. A change in mining operations or specific processes may result in a change in the characteristics of an airborne contaminant which may require more frequent surveys. For example, if the temperature of a process increases, more gas may be released, thus requiring more frequent surveys.
- 4. An issue identified during an inspection, or routine or special maintenance of equipment including the engineering controls, may require more frequent surveys. For example, if an inspection, or routine maintenance, indicates that a dust collection system is not working properly, e.g., leaking, or not performing according to the manufacturer's specification, then more frequent surveys may be warranted.
- 5. Miner-identified issues or complaints or miner-reported illness or injuries may suggest the need for more frequent surveys.

IV. Verification

The exposure monitoring standard does not require recordkeeping. However, the following are examples of what an inspector should look for to determine if surveys are being conducted.

- 1. **Exposure sampling records:** An operator's exposure sampling records may be used to show that surveys are being conducted. Note that any records provided by the operator cannot be used to determine compliance with the TLVs or PEL under sections §§ 56/57.5001(a) or (b).
- 2. **Maintenance records:** Records showing inspection or maintenance of equipment, especially equipment used to control hazards, may be used to show that surveys are being conducted.
- 3. **Workplace inspection records:** Any records of workplace inspections may be used to show that surveys are being conducted.
- 4. **Injury, illness, and/or incident tracking reports:** These reports can also be used as evidence that surveys are being conducted.
- 5. **Interviews:** Inspectors can ask operators and miners of their knowledge of surveys. Inspectors can ask about the type of surveys being conducted, the jobs that are surveyed, the air contaminants that are monitored, and how often surveys are conducted. This information may be used to show that surveys are or are not being conducted.
- 6. **Visual inspection**: The appearance of the work area may help inspectors determine if surveys are being conducted. For example, the presence of visible dust, or accumulations or spillage of potential airborne contaminants may indicate that surveys are not being conducted or are not conducted as frequently as necessary.

V. Inspection Procedures

- 1. Inspectors should first determine which airborne contaminants under §§ 56/57.5001(a) or (b) the operator is required to survey. This can be done through MSHA's exposure sampling, review of the safety data sheets (MSDSs), or a visual inspection of the contaminants or conditions on site. Note: The inspector does not need to demonstrate an exposure over the TLV or PEL under sections §§ 56/57.5001(a) or (b) to determine compliance with §§ 56/57.5002. Compliance under §§ 56/57.5002 should be evaluated under the reasonably prudent person criterion, i.e., what actions a reasonably prudent person familiar with all the facts, including those peculiar to the mining industry, would take in order to provide the protection intended by the standard?
- 2. Inspectors should next determine whether surveys are being conducted by the operator.
- 3. Inspectors should also determine the types of surveys that are being conducted for the airborne contaminants identified in the first step. Identification or verification of the types of surveys can be achieved using the examples provided in sections II and IV, respectively.
- 4. The inspector should also determine if the surveys are adequate. Previous sampling completed by MSHA can provide information as to the adequacy of surveys. For example, if MSHA sampling indicates an exposure near or above the TLV/PEL and the operator is only conducting visual inspections as surveys, then these surveys alone may not be sufficient to determine the adequacy of control measures. In addition, the following two measures may provide information as to the adequacy of surveys.
 - a. Whether surveys are being conducted by a person that is properly trained.
 - b. Whether exposure sampling, consisting of air or wipe samples, is being conducted in accordance with established scientific industrial hygiene principles. MSHA lists sampling methods for each contaminant in Chapter 3 of this manual.
- 5. Inspectors should then determine whether the surveys are being conducted as frequently as necessary using the criteria in section III.
- 6. Inspectors must make a compliance determination based on the facts and information collected from evaluating the operator's activities, or lack thereof. A compliance determination can be made by the inspector individually or in collaboration with the Agency's health and technical staff.
- 7. A sample checklist is provided in Appendix 6A to assist in determining compliance with 30 C.F.R. §§ 56/57.5002.
- 8. The scenarios in Appendix 6B provide common situations with recommended dispositions and Appendix 6C provides sample citations, when warranted, based on those applicable scenarios.

Metal/Nonmetal Health Inspection Procedures Handbook

9. When multiple violations exist, only one citation will be issued. However, the inspector must list all of the air contaminants for which surveys are not being conducted.

Appendix 6A 30 C.F.R. §§ 56/57.5002 Sample Compliance Checklist

1. What are the air contaminant	s that may require surveys? Excl	ude diesel particulate matter and rac	lon
(For Example: type of materi	al mined, previous MSHA exposi	ure sampling, on-site MSDSs, etc.)	

2. Is the operator conducting one or more of the following surveys for air contaminants? How frequently are they being conducted?

Survey Type	Yes/No	Air Contaminant(s)	Frequency
Exposure			
Sampling			
(quantitative)			
Workplace			
Inspections			
(qualitative)			
Equipment			
Inspections			
(qualitative)			
Injury, Illness, &			
Incident Tracking			
Miner Interview			
and Input			
Occupational			
Health Assessments			
Other Survey			
Methods			

3. Does the operator use one or more of the following criteria to determine frequency?

Parameter that Impacts Frequency	Yes/No
Sample results	
Changes in the job/task/equipment	
Changes to the hazard (process)	
Results of inspections	
Miner input	
Injury/illness/incident reports	

Appendix 6B Scenarios

Note: These scenarios are examples only. These determinations are not requirements. Because mines are ever changing, the inspector must determine how that mine actually complies with the standard based on the current facts.

■ Scenario 1: An inspector is inspecting a metal mine where mercury (Hg) and hydrogen sulfide (H2S) by-products are known to exist and there is the potential for exposure. There is no history of overexposures to either contaminant from MSHA's compliance sampling results. The inspector asks the operator if he is doing surveys for mercury and hydrogen sulfide to ensure controls are adequate. The operator stated that he has never considered the need to conduct surveys and has no idea of the health hazards related to mercury or hydrogen sulfide. The miners state that surveys have never been done. Finally the operator acknowledges the presence of the chemicals and that he knows there is a standard but states again that he didn't see a need to conduct any surveys.

A 56/57.5002 citation is warranted since it is clear that the operator is not doing any surveys. Note that this is determined regardless of any 56/57.5001 exposure sampling the inspector may or may not conduct during the inspection to determine compliance with the TLVs. Negligence may be "high" because the operator knew (or should have known) of the existence of the chemicals and that surveys were not being conducted and there are no mitigating circumstances. Note that only one citation would be issued, listing both contaminants.

Scenario 2: At an underground lead mine, an inspector takes a personal air sample for lead to determine compliance under 57.5001(a), and also asks for evidence of surveys being conducted in accordance with 57.5002. The operator states that they do not take any lead air samples. However, the operator states that miners take annual physicals where blood lead levels are assessed. The operator also says that the ventilation and dust collection systems are inspected and serviced routinely and are all working according to manufacturer's specifications. Finally, the operator states that supervisors conduct daily walk-through inspections to ensure that no unsafe conditions exist. Upon analysis of the MSHA air samples, there is no overexposure for lead under section 57.5001(a).

In this scenario, it is clear that surveys are being conducted even though the operator has not conducted its own industrial hygiene exposure sampling. The operator is conducting occupational health surveillance as well as equipment and workplace inspections. These surveys are also being conducted as frequently as necessary to verify adequacy of controls, which is supported by the inspector's sampling results. The operator is in compliance with section 57.5002.

■ Scenario 3a: The inspector takes samples at a large aggregate mine for respirable silica dust and also asks the operator for evidence of any surveys conducted. The operator shows the inspector his past three years of exposure sampling which includes routine sampling of the miners in those jobs where silica exposures are expected. The mine operator has identified those jobs that have potentially high silica exposures and has also periodically recorded their low personal exposures. The MSHA sampling results are received and one sample indicates an exposure greater than the TLV times the error factor which results in a citation being issued for a violation of section 56.5001(a).

In this scenario, there is sufficient evidence that the operator is conducting surveys as frequently as necessary to determine the adequacy of controls. The operator has demonstrated a functional exposure assessment strategy by monitoring and recording results of those miners with potential exposures to silica. Note however that even though the inspector issued a citation for a violation of section 56.5001(a) for the single overexposure, the operator is in compliance with section 56.5002 because the exposure assessment system appears sufficiently frequent to determine the adequacy of controls.

■ Scenario 3b: Similar to the previous aggregate mine scenario (3a), an operator states he has taken two respirable silica dust samples but none in the past year. Only those two samples are given as evidence of surveys that have been conducted in the past three years. The mining method produces silica dust and the operator's two samples showed exposures near the TLV. The inspection notes visible airborne dust and accumulations. An MSHA personal air sampling result indicates an overexposure to silica with subsequent issuance of a citation for violation of section 56.5001(a).

The facts suggest that although surveys are being conducted, they are not being conducted as frequently as necessary to determine the adequacy of controls for this mining method, as evidenced by the visible dust and accumulations and the operator's own sample results. In this case, the inspector would issue a citation under section 56.5002, inasmuch as the violation is supported by the MSHA sample.

■ Scenario 4: During an underground (UG) mine inspection, a miner is discovered welding in a shop. The inspector notes that the engineering local exhaust ventilation (LEV) fume/dust controls are not performing in accordance with the manufacturer's specifications. The inspector determines through observation and operator interview that surveys are not being conducted to ensure satisfactory LEV performance and determine the miner's welding fume exposure. In addition, the inspector immediately takes a personal welding fume sample and later finds that the iron oxide fume concentration exceeds the TLV mandated in accordance with section 57.5001(a).

The operator was not conducting any qualitative or quantitative surveys. Although an exposure exceeding the TLV is not required to determine non-compliance with 57.5002, it supports the evidence that the operator is not conducting surveys or not conducting them as frequently as necessary to ensure the adequacy of the controls. Along with a 57.5001(a) violation, the evidence supports a citation for a violation of section 57.5002 in this scenario.

■ Scenario 5: An inspector was investigating an injury report where a miner was hospitalized for carbon monoxide poisoning. Upon completion of the investigation, the inspector determined that an overexposure more than likely occurred due to an inadequately ventilated gasoline-powered air compressor. The compressor was in a shop and provided pneumatic air to a hand-held sander. The compressor has a plate indicating it should not be used in an enclosed area due to potential exposure to carbon monoxide. The inspector did not take an exposure sample since the incident had already occurred, but he determined that no surveys for carbon monoxide had been conducted during the operation of the compressor.

Metal/Nonmetal Health Inspection Procedures Handbook

Based on the evidence that no surveys for CO were conducted, a citation for a violation of section 56.5002 would be warranted. In addition, the Injury/Illness would be listed as Occurred and Fatal since carbon monoxide poisoning could have resulted in death. This would result in an S&S citation. In this scenario, the Negligence would be High since the operator knew or should have known (by the info on the plate) of the potential hazard and did not conduct surveys to determine the adequacy of controls to ensure miners' exposures did not exceed the TLV.

Appendix 6C Example Citations and Terminations

Note: These Citations and Terminations correlated to the Scenarios are examples only. These determinations are not requirements. Because mines are ever changing, the inspector must determine how the mine actually complies with the standards based on the current facts.

Scenario 1	Page 6A-6, 7
	Page 6A-8, 9
Scenario 4.	Page 6A-10, 11
Scenario 5	Page 6A-12, 13

Mine Citation/Order APPENDIX 6C	U.S. Department of Labor Mine Safety and Health Administration
Section I–Violation Data	
1. Date Mo Da Yr Jan 10, 2013 2. Time (24 Hr. Clock) 13:30	3. Citation/ Order Number 1000014
John Doe	5. Operator AAA Mining
6. Mine Acme Mine	7. Mine ID 01-23456 (Contractor)
8. Condition or Practice	8a. Written Notice (103g)
mercury and hydrogen sulfide from the reactors when on the systems. The operator stated he has never conducted. No evidence was available that survey	
O Marie Company Company Company	See Continuation Form (MSHA Form 7000-3a)
Safety of Act T	art/Section of title 30 CFR 56.5002
Section II–Inspector's Evaluation	
10. Gravity: A. Injury or Illness (has) (is): No Likelihood ☐ Unlikely ■	Reasonably Likely Highly Likely Occurred
B Injury or illness could rea-	ays Or Restricted Duty Permanently Disabling Fatal
C. Significant and Substantial: Yes No ■	D. Number of Persons Affected: 3
	oderate D. High E. Reckless Disregard
12. Type of Action 104a 13. Type of Issuance	(check one) Citation Order Safeguard Written Notice
14. Initial Action A. Citation B. Order C. Safeguard D. Written Notice	E. Citation/ Order Number F. Dated Mo Da Yr
15. Area or Equipment	
16. Termination Due A. Date Mo Da Yr Jan 17, 2013 B. Time (24 Hr. Clock)	13:30
Section III—Termination Action	
17. Action to Terminate	
18. Terminated A, Date Mo Da Yr B. Time (24 Hr. Clock)	
Section IV—Automated System Data	24 Disease as Mill
19. Type of Inspection (activity code) E01 20. Event Number 2000002	21. Primary or Mill
22. Signature	23. AR Number [1588
	usiness Regulatory Enforcement Fairness Act of 1996, the Small Business Administration has

MSHA Form 7000-3, Apr 08 (revised) In accordance with the provisions of the Small Business Regulatory Enforcement Fairness Act of 1996, the Small Business Administration has established a National Small Business and Agriculture Regulatory Ombudsman and 10 Regional Fairness Boards to receive comments from small businesses about federal agency enforcement actions. The Ombudsman annually evaluates enforcement activities and rates each agency's responsiveness to small business. If you wish to comment on the enforcement actions of MSHA, you may call 1-888-REG-FAIR (1-888-734-3247), or write the Ombudsman at Small Business Administration, Office of the National Ombudsman, 409 3rd Street, SW MC 2120, Washington, DC 20416. Please note, however, that your right to file a comment with the Ombudsman is in addition to any other rights you may have, including the right to contest citations and proposed penalties and obtain a hearing before the Federal Mine Safety and Health Review Commission.

Mine C	itation/Order uation	APPEN	NDIX 6C			partment of Lab			
Section I-	Subsequent Action/	Continuation Data							
1. Subse	equent Action 1a.	Continuation	2. Dated (Original Issue)	Mo Da Jan 10, 2		3. Citation/ Order Number	1000014-1		
4. Serve	John Do	е			5. Operato	AAA Mining			
6. Mine	Acme Mine				7. Mine ID	01-23456		(Contractor)	
Section II-	-Justification for Acti	on							
	nine operato ot overexpos		ng surveys to	determine	the ade	quacy of conti	rol measures to	ensure miners	5
									i
							*		-
				EXAM	PLE				
								,	
0		- T-1						See Continuation F	orm
8. Exten	ISubsequent Action ded To A. Date	Mo Da Yr	B. Time (24 Hr. Cl	ock)		C. Vacated	D. Terminated	E. Modified	
	/Inspection Data								
9. Type E15	of Inspection	[10. E	Event Number 200	00002					
11. Sign			AR Ni 158		12. Date	Mo Da Yr Jan 17, 2013	13. Time (24 Hr. C	12:00	
MSHA Fo	orm 7000-3a, Mar 85	(revised)	•						

Mine Citation/Order APPENDIX 6C	U.S. Department of Labor Mine Safety and Health Administration
Section I–Violation Data	
1. Date Mo Da Yr Jan 8, 2014 2. Time (24 Hr. Clock) 14:30	3. Citation/ Order Number 1000015
4. Served To Bob Smith	5. Operator Red River Mining
6. Mine Canyon Mine	7. Mine ID 12-98765 (Contractor)
8. Condition or Practice	8a. Written Notice (103g)
adequacy of control measures. The mining process e were observed along with one inch thick settled ac revealed an overexposure to respirable silica-bearin operator within the last three years showed high leve the controls in place were adequate.	ist surveys as frequently as necessary to determine the mits silica-bearing dust. Clouds of visible airborne dust cumulations on surfaces. MSHA sampling 12/20/2013 ig dust. The previous two dust samples taken by the ls of silica and were not frequent enough to determine if
	VIIII EE
	See Continuation Form (MSHA Form 7000-3a)
	art/Section of title 30 CFR 56.5002
Section II–Inspector's Evaluation	
10. Gravity:	Become blad State Comment Comm
A. Injury or Illness (has) (is): No Likelihood Unlikely B. Injury or illness could reasonably be expected to be: No Lost Workdays Lost Workd	Reasonably Likely Highly LIkely Occurred ays Or Restricted Duty Permanently Disabling Fatal Fatal
C. Significant and Substantial: Yes No No	D. Number of Persons Affected: 10
11. Negligence (check one) A. None B. Low C. Mc	oderate D. High E. Reckless Disregard
12. Type of Action 104a 13. Type of Issuance	(check one) Citation Order Safeguard Written Notice
14. Initial Action A. Citation B. Order C. Safeguard D. Written Notice	E. Citation/ Order Number F. Dated Mo Da Yr
15. Area or Equipment	
16. Termination Due A. Date Mo Da Yr Jan 28, 2014 B. Time (24 Hr. Clock)	23:59
Section III—Termination Action	
17. Action to Terminate	
18. Terminated A. Date Mo Da Yr B. Time (24 Hr. Clock)	
Section IV—Automated System Data	
19. Type of Inspection (activity code) E01 20. Event Number 2000001	21. Primary or Mill
22. Signature	23. AR Number 1689
MSHA Form 7000-3, Apr 08 (revised) In accordance with the provisions of the Small B established a National Small Business and Agriculture Regulatory Ombudsman and 10 Re	usiness Regulatory Enforcement Fairness Act of 1996, the Small Business Administration has gional Fairness Boards to receive comments from small businesses about federal agency

MSHA Form 7000-3, Apr Us (revised) In accordance with the provisions of the Small Business Regulatory Emoticement Fairness Act of 1995, the Small Business and Agriculture Regulatory Ombudsman and 10 Regional Fairness Boards to receive comments from small businesses about federal agency enforcement actions. The Ombudsman annually evaluates enforcement activities and rates each agency's responsiveness to small business. If you wish to comment on the enforcement actions of MSHA, you may call 1-888-REG-FAIR (1-888-734-3247), or write the Ombudsman at Small Business Administration, Office of the National Ombudsman, 409 3rd Street, SW MC 2120, Washington, DC 20416, Please note, however, that your right to file a comment with the Ombudsman is in addition to any other rights you may have, including the right to contest citations and proposed penalties and obtain a hearing before the Federal Mine Safety and Health Review Commission.

Mine Citation/Order APPENT Continuation	JIX OC	U.S. Department of Labor Mine Safety and Health Administration	
Section I-Subsequent Action/Continuation Data			
Subsequent Action 1a. Continuation	2. Dated Mo [(Original Issue) Jan 8	2014 3. Citation/ Order Number 1000015-1	
4. Served To Bob Smith		5. Operator Red River Mining	
Canyon Mine		7. Mine ID 12-98765	(Contractor)
Section II—Justification for Action			
The mine operator has increa exposure to respirable silica-l sampling determined no over	earing dust. (Furthern	urveys necessary to adequately contr nore, the analytical result of MSHA's silica-bearing dust).	ol miners' 01/14/2014 re-
	EXAMI	PLE	
Section III-Subsequent Action Taken			See Continuation Form
B. Extended To A. Date Mo Da Yr	B. Time (24 Hr. Clock)	C. Vacated D. Terminate	ed E. Modified
Section IV—Inspection Data			
9. Type of Inspection 10.	Event Number 2000001		
11. Signature	AR Number 1689	12. Date Mo Da Yr 13. Time (24 Hr	7. Clock) 17:00
MSHA Form 7000-3a, Mar 85 (revised)	1,2009	1 2011 2011	

Mine Citation/Order APPENDIX 6C		rtment of Labor y and Health Administration
Section I–Violation Data		
1. Date Mo Da Yr Jan 14, 2014 2. Time (24 Hr. Clock) 16:50		3. Citation/ Order Number 1000017
4. Served To Mark Sharp	5. Operator	Mountain Mining Inc.
6. Mine Whistle Mine	7. Mine ID	15-54321 (Contractor)
8. Condition or Practice		8a. Written Notice (103g)
Scenario 4: The operator failed to conduct surveys to the personal exposure levels of a miner performing ventilation fans located near the work bench were naway from the miner's breathing zone. The opera sampled by MSHA on 1/3/2014 with results revealing to the conduct surveys to the personal sampled by MSHA on 1/3/2014 with results revealing to the conduct surveys to the personal sampled by MSHA on 1/3/2014 with results revealing to the conduct surveys to the personal sampled by MSHA on 1/3/2014 with results revealing to the conduct surveys to the personal exposure sampled by MSHA on 1/3/2014 with results revealing to the conduct surveys to the personal exposure sampled by MSHA on 1/3/2014 with results revealing to the conduct surveys to the personal exposure sampled by MSHA on 1/3/2014 with results revealing to the conduct surveys to the personal exposure sampled by MSHA on 1/3/2014 with results revealing to the conduct surveys to the conduct survey	welding. not function ntor had n	At the time of the inspection the UG shop nal and welding fumes were not being drawn not been conducting surveys. The miner was
		See Continuation Form (MSHA Form 7000-3a)
Safety of Act T	Part/Section of itle 30 CFR	57.5002
Section II—Inspector's Evaluation 10. Gravity:		
A. Injury or Illness (has) (is): No Likelihood Unlikely	Reasonably L	ikely Highly Likely Occurred
B. Injury or illness could rea-	lays Or Restrict	
C. Significant and Substantial: Yes ☐ No ■		D. Number of Persons Affected: 1
11. Negligence (check one) A. None B. Low C. Mc	oderate 🔳	D. High E. Reckless Disregard
12. Type of Action 104a 13. Type of Issuance	(check one)	Citation Order Safeguard Written Notice
14. Initial Action A. Citation B. Order C. Safeguard D. Written Notice	E. Citation/ Order Num	ber F. Dated Mo Da Yr
15. Area or Equipment		
16. Termination Due A. Date Mo Da Yr Jan 28, 2014 B. Time (24 Hr. Clock)	17:00	
Section III-Termination Action		
17. Action to Terminate		
18. Terminated A. Date Mo Da Yr B. Time (24 Hr. Clock)		
Section IV—Automated System Data		
19. Type of Inspection (activity code) E01 20. Event Number 2000003		mary or Mill
22. Signature		23. AR Number 1689
MSHA Form 7000-3, Apr 08 (revised) In accordance with the provisions of the Small B established a National Small Business and Agriculture Regulatory Ombudsman and 10 Re		ory Enforcement Fairness Act of 1996, the Small Business Administration has loards to receive comments from small businesses about federal agency

MSHA Form 7000-3, Apr 08 (revised) In accordance with the provisions of the Small Business Regulatory Enforcement Fairness Act of 1996, the Small Business Administration has established a National Small Business and Agriculture Regulatory Ombudsman and 10 Regional Fairness Boards to receive comments from small businesses about federal agency enforcement actions. The Ombudsman annually evaluates enforcement actions of MSHA, you may call 1-888-REG-FAIR (1-888-734-3247), or write the Ombudsman at Small Business Administration, Office of the National Ombudsman, 409 3rd Street, SW MC 2120, Washington, DC 20416. Please note, however, that your right to file a comment with the Ombudsman is in addition to any other rights you may have, including the right to contest citations and proposed penalties and obtain a hearing before the Federal Mine Safety and Health Review Commission,

Mine Citation/Order APPENDIX 6C U.S. Department of Labor Continuation Mine Safety and Health Administration								
Section I-Subsequent Ac	tion/Continuation Data							
Subsequent Action		2. Dated (Original I	Mo Da ssue) Jan 14,		3. Citation/ Order Number	000017-1		
4. Served To Mark	Sharp			5. Operato	Mountain Mi	ning Inc.		
6. Mine Whistle I	Mine			7. Mine ID	15-54321		(Contractor)	
Section II-Justification for	Action							
Surveys are be control fans ha (Results of MSI Value (TLV)).	ve been replac	ced and are	working to ex	khaust ird	on oxide fumes	from the ben	ch work area.	
			EXAM	PLE				
İ								
								-
								- 1
							See Continuation Fe	 om []
Section III-Subsequent A	ction Taken							
8. Extended To A. Da	te Mo Da Y	B. Time (24	Hr. Clock)		C. Vacated	D. Terminated	E. Modified	
Section IV-Inspection Da								
9. Type of Inspection E15	10.	Event Number	2000003					
11. Signature			AR Number	12. Date	Mo Da Yr	13. Time (24 Hr. C	12:00	
			1689		Jan 28, 2014		12.00	

MSHA Form 7000-3a, Mar 85 (revised)

Mine Citation/Order APPENDIX 6C	U.S. Department of Labor Mine Safety and Health Administration						
Section I-Violation Data	2 Citation						
1. Date Mo Da Yr Jan 25, 2013 2. Time (24 Hr. Clock) 10:50	3. Citation/ Order Number 1000018						
4. Served To Mike Brown	5. Operator Star Mining						
6. Mine Sun Mine	7. Mine ID 04-45678 (Contractor)						
8. Condition or Practice	8a. Written Notice (103g)						
Scenario 5: Dust, gas, mist, and fume surveys were not being conducted to determine the extent of exposure to airborne contaminant carbon monoxide (CO) in the mine shop where a gasoline-powered air compressor was being used to power a hand-held sander. The Production Manager ordered the compressor placed inside the mine shop due to icing problems in the air lines when located outdoors, ignoring visible warnings on the compressor and in the operators manual regarding risk of asphyxiation when used in an enclosed unventilated area. No surveys for CO were conducted during operation of the compressor. A miner was overcome by CO on 1/24/2013 at approximately 12:30 and was hospitalized for treatment. The Production Manager engaged in aggravated conduct constituting more than ordinary negligence in that he knew or should have known about surveys and miners were potentially exposed to CO. This violation is an unwarrantable failure to comply with a mandatory standard.							
	See Continuation Form (MSHA Form 7000-3a) art/Section of the 30 CFR 56.5002						
Section II–Inspector's Evaluation							
10. Gravity:	Because his library D. History D. Consumed D.						
A. Injury or Illness (has) (is): No Likelihood Unlikely B. Injury or illness could rea-	Reasonably Likely Highly LIkely Occurred ays Or Restricted Duty Permanently Disabling Fatal Fatal						
sonably be expected to be: C. Significant and Substantial: Yes No	D. Number of Persons Affected: 1						
	oderate D. High E. Reckless Disregard						
12. Type of Action 104(d)(1) 13. Type of Issuance							
14. Initial Action A. Citation B. Order C. Safeguard D. Written Notice	E. Citation/ Order Number						
15. Area or Equipment							
16. Termination Due A. Date Mo Da Yr Jan 25, 2013 B. Time (24 Hr. Clock)	17:00						
Section III—Termination Action							
17. Action to Terminate							
18. Terminated A. Date Mo Da Yr B. Time (24 Hr. Clock)							
Section IV—Automated System Data							
19. Type of Inspection (activity code) E07 20. Event Number 2000004	21. Primary or Mill						
22. Signature	23. AR Number 4909						
MSHA Form 7000-3, Apr 08 (revised) In accordance with the provisions of the Small B established a National Small Business and Agriculture Regulatory Ombudsman and 10 Re enforcement actions. The Ombudsman annually evaluates enforcement activities and rate enforcement actions of MSHA, you may call 1-888-78E-5-FAIR (1-888-734-3247), or write the	s each agency's responsiveness to small business. If you wish to comment on the						

entorcement actions of MSHA, you may call 1-abs-REU-FAIR (1-abs-134-3241), of while the United at State at State and State at Sta

Mine Citation/Order A Continuation	PPENDIX 6C			artment of Lal ety and Health	bor Administration		
Section I-Subsequent Action/Continuation				-			
1. Subsequent Action 1a. Continua		lan 25, 20	013	Citation/ Order Number	1000018-1		
4. Served To Mike Brown			5. Operator	Star Mining	1	н	
6. Mine Sun Mine			7. Mine ID	04-45678		(Contractor)	
Section II-Justification for Action							
The mine operator has r time carbon monoxide n properly.							:d
	E 7	V A B 4 I					
	, E2	XAMF	LE				
	*						
	·						
Continue III Colonomical Antinue Tolon						See Continuation F	orm
8. Extended To A. Date Mo D	Da Yr B. Time (24 Hr. Clock)			C. Vacated	D. Terminated	E. Modified	
Section IV-Inspection Data		L			*		
9. Type of Inspection	10. Event Number 20000	04					
E15 11. Signature	AR Numbe		2. Date	Mo Da Yr	13. Time (24 Hr.	Clock)	
Signaturo	4909			Jan 25, 2013		15:30	

June 2014 6A-13

MSHA Form 7000-3a, Mar 85 (revised)